PICCOLO

GRADE 3 INTERNAL SOUNDER



This remotely powered sounder features a piezo sounder and two bright LED's for audible and visual indication. The sound output is selectable for either alternating or continuous tone. It is also protected against tampering by means of lid removal and removal from the mounting surface.

- Grade 3 Environment Class IV
- Low profile design
- 115dB Sound output
- Selectable alternating or continuous tone
- Flashing alarm indication
- Low current consumption
- Tamper protected lid and mounting
- Can be installed in security systems up to and including Grade 3

Piccolo Specifications

Nominal Power Supply:	12v DC	**Flash only Current:**	17mA @ 12v DC
Voltage Range:	9-15v DC	**Sound and Flash:**	100mA @ 12v DC
Sounder Type:	Piezo	**Temperature Range:**	-15°C - +40°C
Sound output level:	115dB(A) @ 1 Metre	**Material:**	Polycarbonate
Sound only Current:	84mA @ 12v DC	**Dimensions:**	125mm x 85mm x 37.5mm

Contact us:

Phone:
Tel: +44(0)151 6061000
Fax: +44(0)151 6061122

Online:
Web: www.cqr.co.uk
Email: info@cqr.co.uk

Address: CQR Fire & Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK.